

TECHNICAL DATA

Voltage	Nominal Supply	24 V DC 18-32 V DC
Power consumption	Nominal	1-3 A (varies with the sign size)
Data communication		RS 485
EMC	EU Directive	89/336/EEC and 2006/28/EG CE and e mark EN50155
Ambient environment	Temperature range Relative humidity Shock, Vibration	-30 to +70°C <93% RH at +40°C EN 50155:1995 EN 61373
LEDs	Description Pitch (H x L in mm)	4 mm amber 10,4 x 10,0

We reserve the right to change the technical specification without prior notice.

mobitec
A WORLD OF SIGNS

Mobitec AB

Box 97, Ölltorp Industriområde • SE-524 21 Herrljunga, Sweden
Phone +46 (0)513-229 00 • Fax +46 (0)513-107 22 • www.mobitec.eu • info@mobitec.eu

SWEDEN • BRAZIL • GERMANY • INDIA • AUSTRALIA

Doc. No. 02832-R1-Eng-2010

MobiLED – SmartFit



MobiLED SmartFit is an extremely versatile sign. The unit can be mounted in the conventional manner or, due to its ultra slim construction, it can be bonded to glass or other substrates where space is of a premium. The SmartFit sign therefore is a very cost effective solution since it helps to reduce installation cost significantly.

MobiLED SmartFit is a slim, neat sign that can be fitted without a box or cover. The smart sign still offers the same functionality and legibility as all the other MobiLED signs. It has a built-in light sensor that adjusts to the appropriate intensity to suit the ambient light conditions. The high intensity amber LEDs feature a wide viewing angle and high resolution for optimal legibility.

FEATURES

- Rail qualified
- Fully electronic
- Slim-line housing
- Built-in light sensor
- UV-protection
- Illumination for longer stops

BENEFITS

- Reduced life cycle cost
- Optimal intensity and legibility
- Adhesive bonding
- No extra brackets
- Compatible
- Robust and resistant
- Light weight
- Fits instantly into passenger compartment
- Maintenance free