



Technical data INFOtainment SMART-Design 35.8" (Bus)

Size	35.8"
Resolution	1.920 x 534 (Full-HD xn)
Active Display Area	878 mm x 240 mm
Aspect Ratio	16 : 4.4
Brightness	up to 1.600 cd/m ² (Nits)
Backlight-Illumination	LED
Contrast Ratio	10.000 : 1
Viewing Angle	horizontal: 178°, vertical: 178° ultra-wide viewing
Display Colours	16.7 M, 24 Bit
Colour / Surface / Material	anodized aluminum
Weight	approx. 12.6 kg
Operating Temperature Range	0°C ... +50°C (depending on design and vehicle integration)
Storage Temperature Range	-20°C ... +60°C
Operating Voltage	24 V-DC (16,8 V ... 32 V)
Power Consumption	-
Interfaces	digital (DVI / DP), IP/Ethernet (M12), IBIS (VDV 300), USB, STOP-Signal, Audio Line-Out (depending on model)
Operating System	Linux
Standards	EMC Regulation ECE-R10 Flammability Regulation ECE-R118

Sunlight readable screen

Elegant aluminium profile

**Brilliant display of text, graphics
and images**

Toughened safety glass

Fanless

Service-friendly design

Low weight

Low heat emission

**TFT with LED-backlight and
Wide Viewing Angle technology**

Maintenance-free