





## Technical data SICMA-Control

Operating voltage	24 V-DC (16,8 - 32 V)
Power consumption	max. 1,5 A
Operating/storage temperature	- 40 °C to +70 °C / - 40 °C to +80 °C
Display	graphic display with 32 x 122 pixels, rear lit
Dimensions	(H x W x D) approx. 51 x 180 x 140 mm
Interfaces	IBIS vehicle bus (VDV300) (master-slave-interface), LAWO mono bus / alphabus optional: Ethernet 10/100 BaseT RS232 RS485/RS422/CAN
Software	TED <sup>®</sup> plus, InfoTED <sup>®</sup> (MS-operating systems WIN95 - WIN XP, WIN Vista)
Loading of operating data	- <b>manually</b> with PC-Card (PCMCIA - SRAM or Flash) - <b>automatically</b> via Ethernet-Interface (WLAN, FTP service)* *depending on version
Standards and directives	VDV 300 (IBIS)
	<b>Bus:</b> EMC <b>Directive</b> 2005/83/EG
	<b>Type approval number:</b>  034652 e1*72/245*2005/83*4652*00
	<b>Regulation ECE-R10</b> <b>Approval number:</b>  10 R - 024652
	Burning Behavior <b>Directive</b> 95/28/EG