



Technical data **MobiMASTER ICU 602**

| | |
|---------------------------------|--|
| Operating voltage | 24 VDC (9 - 36 VDC) |
| Power consumption | max. 0.2 A at 24 VDC |
| Operating temperature | - 25 °C to + 70 °C |
| Display | LCD graphic display, 64 x 256 pixels |
| Dimensions | 178 x 50 x 115 (L x H x D, installation dimensions in mm without front panel) |
| Weight | 620 g |
| Interfaces | standard: RS485, digital I/O, RS232, USB optional: IBIS Slave, IBIS Master, GPS, Ethernet, Audio |
| Editing software | MIE (MobilInfoEdit) |
| Data update | manually via USB flash memory automatically via IP/Ethernet Interface (wireless and FTP service optionally available) |
| Memory capacity | 256 MB |
| Standards and directives | EMC Directive 2006/28/EC Type approval number e5*72/245*2006/28*0245*03 Flammability Directive 95/28/EC Regulation ECE-R118 |

Modern design.

Alphanumeric keyboard with highly user-friendly buttons and backlight.

IP classified front (dust and water protected), optionally also IP classified from the back.

Advanced version includes:

- Next stop information
- Voice announcement function for announcements inside and outside the vehicle
- GPS receiver
- Ethernet Interface
- Automatic triggering via GPS or odometer

Fits into a standard radio slot (ISO 7736).