



Technical data - WHITE LINE -

| | |
|--|--|
| Technology | SMD-LED |
| Color | white |
| Viewing Angle | 120° |
| Resolution | height: up to 32 lines width: up to 240 columns (other resolutions available on request) |
| Operating voltage | 24 V-DC (16,8 - 32V) |
| Brightness | max. 9000 cd/m² |
| Operating / storage temperature | - 20 °C to +70 °C / - 30 °C to +85 °C |
| Lifetime | approx. 100 000 hours (depending on temperature and current) |
| Interfaces | superordinate data bus: VDV300 (IBIS), IP/Ethernet, RS232 subordinate data bus: LAWO-MONO, RS485/422 |
| Editing software | TED®plus |
| Loading of operating data | manually by PC-Card, USB-Stick automatically via IP/Ethernet-Interface (optionally available wireless and FTP service) |
| Standards and directives | VDV 300 (IBIS) EMC Directive 2006/28/EG Type approval number: e1*72/245*2006/28*5058*00 Regulation ECE-R10 Approval number: E1 10 R - 025058 Burning Behavior Directive 95/28/EG Regulation ECE-R118 |

Perfect readability even in difficult conditions

Extraordinary contrast thanks to white LEDs

High energy efficiency and reduced operating costs thanks to low power consumption

LED brightness steplessly adjustable

Premium destination sign with attractive appearance