



Integrated control unit optional

Special features

- Compact, robust design
- Despite compact dimensions, the display can show two lines of text
- Light-weight
- The ideal choice especially for retrofitting
- Optionally integrated control unit with up to 50 memory slots
- Automatic adaption of the light-intensity

MobiLED Compact

This new MobiLED sign has a very compact design, making it the ideal choice for passenger information in a confined space e.g. on minibuses, interurban buses or coaches. Despite the compact dimensions, it offers the option of displaying one or two lines of text. Furthermore, it is simple to install and very easy to read.

The Compact sign is available with or without an integrated control unit on the back of the housing - a new Mobitec variant. With this it is easily possible to enter text directly, using an alphanumeric keyboard. Alternatively, the display is programmed by means of the standard Mobitec Editor MIE- the information is downloaded quickly via USB flash memory. Of course, the display is also compatible with any of our other products. Furthermore, it is the ideal solution for retrofitting: Apart from connecting the power supply, no further cabling is necessary.



Technical Data

Voltage	Nominal operating voltage	12V DC & 24 V DC 9 - 36 V DC
Power consumption	Maximum at 24V supply voltage	0,75 A
Data interface		RS 485
EMC	EU Directive	2006/28/EG (e-mark)
Ambient environment	Temperature range Relative humidity Shock / Vibration	- 25° to +70° C < 93% RH at +40°C EN 50155:1995 EN 61373
LEDs	Description Pitch	4 mm amber 7,62 mm

We reserve the right to change the technical specification without prior notice.