



Technical data **MobiMASTER ICU 402**

Operating voltage	12 VDC or 24 VDC (9 - 32 VDC)
Power consumption	40 mA (standby 30 mA)
Operating temperature	- 20 °C to + 70 °C
Display	LCD graphic display
Dimensions	131 x 67 x 35 (W x H x D)
Weight	140 g
Interfaces	standard: RS485, USB optional: IBIS Slave, RS232, second RS485 Interface, digital I/O
Editing software	MIE (MobilInfoEdit)
Data update	via USB flash memory
Memory capacity	2 MB Flashprom
Standards and directives	VDV 300 (IBIS) EMC Directive 2006/28/EC Type approval number e5*72/245*2006/28*0246*01 Flammability Directive 95/28/EC Regulation ECE-R118

Modern and compact design.

Lightweight.

Logical, intuitive user navigation.

High-resolution LCD display with backlighting.

Easy data transfer via USB port.

Flexible and simple installation.

Optional: adapter for mounting into a standard radio slot (ISO 7736).

Mobitec AB

Ölltorps Industriområde 4, Box 97 · 524 21 Herrljunga · SWEDEN · Phone: +46 513 229 00 · Fax: +46 513 107 22
info@mobitec.eu · www.mobitec.eu
AUSTRALIA · BRAZIL · GERMANY · INDIA · SWEDEN