

Round nozzle RD 100.75



Aurora-Nr./Aurora No.	Merkmale/Attributes
334-220-0022	100mm hose 75 Konvex

Description



AURORA round nozzle to be used as vents especially for footspace, driver and defrost.

AURORARound nozzles are figured by inner and outside part. The inner ring consisting also the blades rotates in an outside frame. This avoids damage and wear of the dash board. Blades lock up the louver. The round nozzles are available in different diameters and mostly with optional hose adaption. Separate hoses and hose adapters in different dimensions are available by request.

please note: the photos do not meet all versions!



Technical details

Luftvolumenstrom airflow-capacity

	$\dot{V}_{\text{Luft/air}}$ [m ³ /h]
bei 7 m/s at 7 m/s	68,5
bei 10 m/s at 10 m/s	97,9
bei 15 m/s at 15 m/s	146,9

- very effective air distribution
- nozzle can be turned 360°
- visible surface VDI 3400/30

Material:

35% Glass fibre reinforced polyamide PA6, black.

conditions: can be used up to 5000 hours at 120°C (248°F) and short-time (about 1 hour) up to 190°C (374°F).

RD 100.42 - RD 100.75 Konvex round nozzle with outside diameter 100mm, hose adaption 42 to 75mm

Same as RD 100.0 Konvex, but with hose connection

Mounting instructions:

Clipping in wall thickness of 3 mm possible.

Screwing with countersunk screw B3,9 mm (DIN ISO 7050)

screw-on area must be flat

Install mounting base then insert rotating bezel until it snaps into retaining position.

We would be pleased to inform you on demand about possible options.

Drawing

